CORNER GUARDS

Knuffi®

Knuffi® Model A

A 1.57" (40 mm)
B 0.98" (25 mm)
C 0.98" (25 mm)





Available Colors: *Black, Black/Yellow, Black/Fluorescent, Black/Photoluminescent, Red/White, White*

Adhesive Options:
Standard *Removable* *Frost*

Knuffi® Model A+

A 2.36" (60 mm)
B 1.97" (50 mm)
C 1.38" (35 mm)





Available Colors: *Black/Yellow, Reflective Red/White, Reflective Black/Yellow*

Knuffi® Model AA

A 1.57" (40 mm)
B 1.42" (36 mm)
C 0.75" (19 mm)
D 0.75" (19 mm)





Available Colors: *Black, Black/Yellow, Red/White, White*

Knuffi® Model E

A 1.02" (26 mm)
B 0.75" (19 mm)
C 0.28" (7 mm)





Available Colors: *Black, Black/Yellow, Red/White, White*

Adhesive Options:
Standard *Removable* *Frost*

Knuffi® Model H

A 1.85" (47 mm)
B 1.37" (35 mm)
C 0.47" (12 mm)



Available Colors: *Black, Black/Yellow, Red/White, White*

Adhesive Options:
Standard *Removable* *Frost*

Knuffi® Model H+

A 2.36" (60 mm)
B 1.89" (48 mm)
C 0.47" (12 mm)



Available Colors: *Black/Yellow, Reflective Red/White*

WARNING AND PROTECTIVE BUMPER GUARDS

TECHNICAL DATA

Profile Body: Recyclable polyurethane foam.

Surface: Polyurethane foam colored by reverse printing and foamed in place so no paint appears on the outside.

Adhesive: All models except Magnetic and Wall Protection Kits are installed using light and ageing resistant, modified acrylic glue.

Adhesion: 21N/inch (25mm)

Temperature Range: -40°F to +212°F (-40°C to 100°C)

Fire Classification: DIN EN 13501-1 / Class E.

Colors:

Lengths: Most Black/Yellow adhesive-fastened models are available in 3' 3-1/4" (1m), 16' 4-3/4" (5m) and up to 164' 0" (50m) lengths. Other colors and installation styles may not be available in all sizes. Please consult Ideal Warehouse Innovations Inc. for more details.

5-year warranty for elasticity and color-fastness. Knuffi® must be fastened according to the installation recommendations. Exclusions include adhesive power and UV resistance.

Surface, pipe and edge guards are also available.

CORNER GUARDS

KNUFFI® MAGNETIC

This smart solution makes temporary installation a breeze! Easily put them on and take them off any dangerous metal surface and let the heavy magnet do the work.

Knuffi® Magnetic Model A

- A 1.57" (40 mm)
- B 0.98" (25 mm)
- C 0.98" (25 mm)
- D 0.079" (2mm)





Available Colors: *Black, Black/Yellow, Red/White, White*

Knuffi® Magnetic Model E

- A 1.02" (26 mm)
- B 0.75" (19 mm)
- C 0.67" (17 mm)
- D 0.079" (2mm)





Available Colors: *Black, Black/Yellow, Red/White, White*

Available in 3' 3-1/4" (1m) lengths only.

WALL PROTECTION KIT

A complete assembly of a Knuffi® protective bumper guard, factory-fitted to a stainless steel backing. Perfect for uneven surfaces and where adhesive won't work well. Can be anchored into virtually any surface.



Corner Kits

- A 1.89" (48 mm)
- B 1.77" (45 mm)
- C 3.94" (100 mm)
- D 1.18" (30 mm)
- E Ø 0.24" (6 mm)

Available Lengths:
19-3/8" (1/2m) or 3' 3-1/4"(1m)

Knuffi® WPK-A+

- A 2.36" (60 mm)
- B 1.38" (35 mm)





Available Colors: *Black/Yellow, Black/Fluorescent, Reflective Red/White, Reflective Black/Yellow*

Knuffi® WPK-H+

- A 2.76" (70 mm)
- B 1.89" (48 mm)
- C 2.36" (60 mm)
- D 0.47" (12 mm)



Available Colors: *Black/Yellow, Black/Fluorescent, Reflective Red/White, Reflective Black/Yellow*

KNUFFI® FLEX

The innovative Knuffi® Flex is much more flexible than standard Knuffi® corner guard profiles and can adapt to angles between 45° and 160°. From almost flat to very sharp, Knuffi® Flex can be applied to protect all the corners.



Knuffi® Flex

- A 45°-160° flexible angle
- B 0.47" (12 mm)
- C 2.16" (55 mm)



Available Colors: *Black/Yellow, Fluorescent Red/Yellow*

KNUFFI® Y

Knuffi®'s Y profile is extra durable with a hollow core that absorbs even more impact. Made of a newly developed PUR foam, this profile can be applied in high traffic areas and provides stronger protection from hits.

Knuffi® Y

- A 2.44" (62.07 mm)
- B 0.39" (10 mm)
- C 0.39" (10 mm)
- D 1.37" (35 mm)



Available Colors: *Black, Black/Yellow, Black/Fluorescent*

Adhesive Options: Knuffi® Frost – Install in as low as 14°F (-10°C) Knuffi® Removable – Remove up to 5 Times!