

Spilfyter Product Instruction Sheet

March18,202408:57AM_V(0)
Page 01

ITEM NUMBER: 440133

PRODUCT TYPE: Grab & Go® Battery Acid Spill Kit

COMPONENTS:

(2 Quarts) KOLOR-SAFE® Liquid Acid Neutralizer (410001)

- (10) 12"x12" Hazmat Pads (S2-71)
- (1oz.) AQUALOCKIT® Polymer (670001)
- (1 pr.) Nitrile Gloves • (1 pr.) Splash Goggles
- (1) Poly Apron
- (1) Trigger Sprayer
- (1) Scoop w/ Detachable Scraper
- (1) Disposal Bag & Twist Tie

INSTRUCTIONS FOR USE:

HOW TO USE KOLOR-SAFE LIQUID ACID NEUTRALIZERS:

1. Evacuate employees from the spill area.
2. Wear personal protective equipment compatible with chemicals involved.
3. Ventilate the contaminated area.
6. Slowly spray or pour the acid neutralizer on the contained spilled acid.

CAUTION: Some HEAT or GASSING OUT may be generated.

7. The color change indicator changes from PURPLE to YELLOW during neutralization.
8. Apply liquid acid neutralizer until the color change indicator first turns a reddish color.
9. Allow neutralized liquid to cool.
10. Soak up remaining neutralized liquid with sorbent materials.
11. Place used sorbents into temporary disposal containers.
12. Wipe up residue with non-woven cloth material.
13. Dispose of all used articles (sorbents, neutralized liquid, etc.) according to local, state and federal regulations.
14. NOTE: Depending on the extent of the clean-up process, additional equipment may be required.

HOW TO USE AQUALOCKIT® SUPER ABSORBENT POLYMER:

1. Evacuate employees from the spill area, if necessary.
2. Wear personal protective equipment compatible with chemicals involved.
3. Ventilate the contaminated area.
4. Determine if the contaminated water, sludge, neutralized acids or bases, etc. are ph neutral (ph 6-7).
5. Sprinkle some of the AQUALOCKIT® onto the neutral spill.
6. Allow the AQUALOCKIT® to absorb the ph neutral liquid.
7. Collect the used AQUALOCKIT® by sweeping, vacuuming, shoveling, etc.
8. Place the used AQUALOCKIT® into a temporary disposal device.
9. Dispose of all used articles according to local, state, and federal regulations.





Spilfyter Product Instruction Sheet

March18,202408:57AM_V(0)
Page 02

Note: AQUALOCKIT[®] solidifier will not gel spills that are not ph neutral. It is strongly recommended that Kolor-Safe dry or liquid neutralizer be used to neutralize the spill prior to use of AQUALOCKIT[®] for maximum performance.

The information provided herein, is provided "as is" with no representations or warranties of any kind, either express or implied, including, but not limited to, the implied warranties of merchantability or fitness for a Particular purpose. You assume total responsibility and risk for your use of these materials. FyterTech Nonwovens Does not warrant the quality, validity, accuracy, or completeness of the materials or that the information Contained in such materials will be error-free, or that defects or inaccuracies will be corrected. FyterTech Nonwovens may make changes to the materials, or to the products or specifications described therein, at any Time without notice. The materials may be out of date, and FyterTech Nonwovens makes no commitment to update the materials or to make any notification of changes.