

SPEAKMAN® SE-1200

Optimus™ Combination Shower and Eye And Face Wash System

EYEWASH FEATURES:

- Independent eyewash & face wash integrated into one, multi-functioning safety unit.
- Aerated sprays for eyewash comfort & innovative face pads for full face cleansing.
- Flip top dust caps, ABS Plastic bowl
- ½ in. NPT female brass, chrome-plated, full flow stay-open ball valve
- Stainless steel push handle activator
- ½ in. NPT female inlet
- 4.9 gpm @ 30 psi

SHOWER FEATURES

- 8 in. yellow plastic showerhead with internal 20 gpm restrictor flow control
- 1 in. NPT female brass, chrome-plated, full flow stay-open ball valve
- Powder coated yellow, aluminum triangular pull rod activator & optional ADA extension
- 1¼ in. IPS galvanized steel piping stanchion & fittings
- 1¼ in. NPT female top or side supply
- 1¼ in. NPT female waste
- High visibility pull rod activates stay-open shower valve & provides hands-free operation
- DuraJade™ powder coated finish on stanchion for durability & enhanced corrosion resistance
- Elevated drain to support easier testing & to eliminate trip hazards
- Includes all components necessary to be installed in either standard height or ADA configuration
- 20 gpm @ 30 psi
- Patent Pending



FINISH:



Yellow DuraJade

COMPLIANCE:

- Certified to ANSI/ISEA Z358.1
- Wheelchair accessible when installed accordingly

OPTIONS:

Add suffix to model #

- | | |
|--------------------------------|-------------------------------|
| • Anti-freeze protection valve | ☐ -FPV |
| • Hand & foot operation | ☐ -HFO |
| • Hand-held spray | ☐ -HS |
| • In-line strainer | ☐ -ILS |
| • P-trap | ☐ -PT |
| • Scald protection valve | ☐ -SPV |
| • Stainless steel pull rod | ☐ -SPR |
| • Stainless steel shower head | ☐ -SSH |

WARRANTY:


- 3 year limited

Architect/Engineer Approval Space:


SPEAKMAN
400 ANCHOR MILL ROAD
NEW CASTLE, DE 19720

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: MARCH 2017

STANDARD INSTALLATION ROUGH-IN DIMENSIONS



ADA INSTALLATION ROUGH-IN DIMENSIONS



SPEAKMAN® SE-125O

Optimus™ Combination Shower and Eye And Face Wash System

EYEWASH FEATURES:

- Independent eyewash & face wash integrated into one, multi-functioning safety unit.
- Aerated sprays for eyewash comfort & innovative face pads for full face cleansing.
- Flip top dust caps, Stainless Steel bowl
- ½ in. NPT female brass, chrome-plated, full flow stay-open ball valve
- Stainless steel push handle activator
- ½ in. NPT female inlet
- 4.9 gpm @ 30 psi

SHOWER FEATURES

- 8 in. yellow plastic showerhead with 20 gpm internal flow restrictor
- 1 in. NPT female brass, chrome-plated, full flow stay-open ball valve
- Powder coated yellow, aluminum triangular pull rod activator & optional ADA extension
- 1¼ in. IPS galvanized steel piping stanchion & fittings
- 1¼ in. NPT female top or side supply
- 1¼ in. NPT female waste
- High visibility pull rod activates stay-open shower valve & provides hands-free operation
- DuraJade™ powder coated finish on stanchion for durability & enhanced corrosion resistance
- Elevated drain to support easier testing & to eliminate trip hazards
- Includes all components necessary to be installed in either standard height or ADA configuration
- 20 gpm @ 30 psi
- Patent Pending

FINISH:



Yellow DuraJade Stainless Steel

COMPLIANCE:

- Certified to ANSI/ISEA Z358.1
- Wheelchair accessible when installed accordingly

OPTIONS:

Add suffix to model #

- | | |
|--------------------------------|-------------------------------|
| • Anti-freeze protection valve | ☐ -FPV |
| • Hand & foot operation | ☐ -HFO |
| • Hand-held spray | ☐ -HS |
| • In-line strainer | ☐ -ILS |
| • P-trap | ☐ -PT |
| • Scald protection valve | ☐ -SPV |
| • Stainless steel pull rod | ☐ -SPR |
| • Stainless steel shower head | ☐ -SSH |

WARRANTY:

- 3 year limited




Architect/Engineer Approval Space:


SPEAKMAN
400 ANCHOR MILL ROAD
NEW CASTLE, DE 19720

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: MARCH 2017

STANDARD INSTALLATION ROUGH-IN DIMENSIONS



ADA INSTALLATION ROUGH-IN DIMENSIONS



SPEAKMAN® SE-1255

Optimus™ Combination Shower and Eye And Face Wash System

EYEWASH FEATURES:

- Independent eyewash & face wash integrated into one, multi-functioning safety unit.
- Aerated sprays for eyewash comfort & innovative face pads for full face cleansing.
- Flip top dust caps, stainless steel eye and face wash unit
- ½ in. NPT female stainless steel full flow stay-open ball valve
- Stainless steel push handle activator
- ½ in. NPT female inlet
- 4.9 gpm @ 30 psi

SHOWER FEATURES

- 8 in. stainless steel showerhead with 20 gpm internal flow restrictor
- 1 in. NPT female stainless steel, full flow stay-open ball valve
- Stainless steel triangular pull rod activator & optional ADA extension
- 1¼ in. IPS stainless steel piping stanchion & fittings
- 1¼ in. NPT female top or side supply
- 1¼ in. NPT female waste
- Pull rod activates stay-open shower valve & provides hands-free operation
- Stainless steel stanchion for added durability & corrosion resistance
- Elevated drain to support easier testing & to eliminate trip hazards
- Includes all components necessary to be installed in either standard height or ADA configuration
- 20 gpm @ 30 psi
- Patent Pending

FINISH:



All Stainless Steel

COMPLIANCE:

- Certified to ANSI/ISEA Z358.1
- Wheelchair accessible when installed accordingly

OPTIONS:

Add suffix to model #


- | | |
|--------------------------------|-------------------------------|
| • Anti-freeze protection valve | ☐ -FPV |
| • Hand & foot operation | ☐ -HFO |
| • Hand-held spray | ☐ -HS |
| • In-line strainer | ☐ -ILS |
| • P-trap | ☐ -PT |
| • Scald protection valve | ☐ -SPV |

WARRANTY:

- 3 year limited



STANDARD INSTALLATION ROUGH-IN DIMENSIONS



ADA INSTALLATION ROUGH-IN DIMENSIONS

