



Available Colors: Black, Black/Yellow



Diamond-Tuff™ Max combines a heavy-duty PVC top surface with a dense closed cell foam base. At a full 1" thick, Diamond-Tuff™ Max provides the ultimate in relief for leg and back discomfort in work applications where standing occurs for long periods of time. A durable diamond pattern top surface adds traction and is easy to sweep or damp mop clean.

Test	Test Description	*Results
ASTM C1028-96	Static Coefficient of Friction	Dry 0.480
Compression Deflection	Compression Deflection	@20 lbs/sq. In. 0.400 @40 lbs/sq. In. 0.557
ASTM D2240-02	Durometer (Shore A)	80
ASTM D1004-94a-03	Tear Strength (Results measured in force to initiate tearing - in lbs.)	51.9 lbs.
ASTM D3884-01	Abrasion Resistance (Results measured in weight loss - %)	@ 1,000 cycles (0.2%)
ASTM E648-08	Critical Radiant Flux	0.53 watts/sq. cm.
CPSC FF 1-70 ASTM D-2859	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

*All testing of Akro® floor matting has been performed by an independent testing laboratory.



Anti-Fatigue



Anti-Slip



Custom

- Thickness: 1"
- Stock Sizes: 2' x 3', 3' x 5', 3' x 12'
- Roll Sizes: 2' x 75', 3' x 75', 4' x 75'
- Custom Sizes: In 2', 3', and 4' widths (up to 75')